



No.12-6, Hu Tsu Rd.,Hu Pei Tsun Lin Kou Hsiang,Taipei Hsien Taiwan 244 ROC. TEL: 886-2-2603-0269 FAX: 886-2-2603-7394

# Specification

## Aceox® AC3000

Chemical Name: Azodicarbonamide

Property	Specification
Appearance	Fine pale yellow powder
Decomposition Temp(°C)	203±3
Gas Volume(ml/g)	218±5
Average Particle(µm)	8-10
Moisture Content(%)	≦0.3
Ash(%)	≤0.3
РН	6.5-7.0

#### **Application:**

AC3000 is the general used high temperature foaming agent. It can be applied in foaming process under room pressure or in compression. Widely applied in plastic and rubber, such as PE(IXPE), PS, EVA, PVC, NBR, SBR, and rubber & plastic blends. It is particularly applicable for coating of PVC, commonly applied in compression molding of PE, extrusion of PVC and compression molding of rubber & plastic compound, for MD injection, hot-pressed small mold and big mold of EVA are also available. Widely used in insulation materials, handle of sports equipment and MD materials

### **Packaging:**

Packed in 25kgs carton lined with plastic bag or in paper drum.

#### **Storage:**

Storage stability is excellent under normal conditions. This product should be stored in a cool dry places, away from fire, spark and heat. If fire, extinguishing use water spray, carbon dioxide or dry chemical powder. Don't attempt manual fire fighting.

**Shelf life:** 6 months